

R46_275_MIN, Film, Metallized Polypropylene, Safety, 2.2 uF, 10%, 275 VAC (X2), 560 VDC, 110C, Lead Spacing = 37.5mm



Dimensions

| | |
|----|-----------------|
| L | 41.5mm +0.3mm |
| H | 22mm +0.1mm |
| T | 11mm +0.3mm |
| S | 37.5mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 1mm +/-0.05mm |

Packaging Specifications

| | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 420 |

General Information

| | |
|------------------------|--------------------------|
| Supplier: | KEMET |
| Series: | R46_275_MIN |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Cut |
| Qualifications: | ENEC, UL, cUL, CQC |

Specifications

| | |
|-------------------------------|---------------|
| Capacitance: | 2.2 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 275 VAC (X2) |
| Voltage DC: | 560 VDC |
| Temperature Range: | -40/+110C |
| Rated Temperature: | 110C |
| Dissipation Factor: | 0.10% 1kHz |
| Insulation Resistance: | 13.6364 GOhms |
| Max dV/dt: | 100 V/us |
| Safety Class: | X2 |