

VSC8254

Dual Channel 1G/10GBASE-KR to SFI Ethernet LAN/WAN PHY with VeriTime™ and Intellisec™

VSC8254 is a dual 1G/10G serial-to-serial Ethernet PHY featuring VeriTime[™] (IEEE 1588v2) and Intellisec[™] (128/256-bit MACsec) encryption. It also supports dual-sided 10GBASE-KR functionality including auto-negotiation and training in a small form factor, low-power FCBGA ideal for a wide array of board-level signal integrity designs and systemlevel IEEE standard compliant (intelligent) Ethernet connectivity.

VeriTime[™] is Microsemi's patent-pending timing technology that delivers the industry's most accurate IEEE 1588v2 timing implementation. It is the only IEEE 1588v2 solution to be validated by major OEMs in real-world tests and adopted as the preferred low-cost upgrade for meeting emerging requirements in 4G/LTE-Advanced (LTE-A).

Intellisec[™] is Microsemi's patent-pending flow-based extension of the IEEE 802.1AE-based, end-to-end MACsec solution for confidential communications over any MEF CE 2.0 Ethernet or MPLS service provider connections. It is the world's first FIPS 197-certified CGM-AES 256-bit strong MACsec, with legacy support for today's CGM-AES 128-bit field deployments. The VSC8254 device supports full line rate encryption at both 1 GbE and 10 GbE speeds over multiple media types.

Target applications for the VSC8254 device include Ethernet switching, IP edge router connectivity, rack mount connectivity through backplane, fiber and copper cable connectivity, and standalone server access (LAN on motherboard designs or separate network adapters).

The VSC8254 device delivers excellent jitter attenuation with low power. It is well-suited for SFP+ modules and direct attach copper cabling as well as challenging backplane interface applications.

Highlights

- Standards supported include
 IEEE 1588v2/Y.1731 OAM (4 ns), IEEE 802.1AE (128/256-bit MACsec), IEEE 802.3ae, IEEE 802.3ap, SFF-8431, ITU-T G.8261, and ITU-T G.8262
- Support for 10G LAN, 10G WAN, and 1G modes
- Support for SFP+ line modules and 10GBASE-KR backplanes
- Internal cross-connect available

Applications

- Two-port serial-to-serial signal conditioning with failover protection
- 10GBASE-KR-compliant backplane transceivers
- Networks requiring high-accuracy time stamping and synchronization
- Encryption, authentication, and data integrity across WAN data center interconnections
- Multi-port XFI/KR to SFI/SFP+ 10 GbE switch cards, router cards, and network





Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi here under is provided "as is, where is" and with all faults, and the entire risk associated with such information. Information provided by Microsemi and together with regard to such information its provided by such information. Information provided in this document or to any products and services at any time without notice.



VSC8254

Dual Channel 1G/10GBASE-KR to SFI Ethernet LAN/WAN PHY with VeriTime™ and Intellisec™

Built-in Self-Test and SyncE

The VSC8254 device provides a complete suite of on-chip instrumentation including built-in self-test (BIST) functions, line-side and client-side circuit loopbacks, pattern generation, and error detection. Its highly flexible clocking options support LAN and WAN operation using a single 156.25 MHz reference clock rate. Support for Synchronous Ethernet (SyncE) is also included.

Range of Support

- IEEE 1588v2/Y.1731 OAM precision timing support at 1.25 Gbps and 10.3 Gbps
- Compliant with IEEE 802.1AE specifications for 128/256-bit MACsec support
- Compliant with IEEE 802.3-2012 and SFF-8431 electrical (SFI) specifications
- 9.95 Gbps WAN and 10.3 Gbps LAN operation, as well as 1.25 Gbps Ethernet support
- Standard SFP+ and QSFP+ applications
- 10GBASE-KR (IEEE 802.3-2012) for 10G backplanes
- Adaptive equalization receiver and programmable multi-tap transmitter pre-emphasis
- SPI, MDIO, and two-wire serial slave management interfaces

Key Specifications

- 1.5 W, typical, for each bidirectional channel
- 1.2 V and 0.97 V core power supplies (2.5 V TTL supply)

Flexibility and Tools

- VScope input signal monitoring integrated circuit
- · Host-side and line-side loopbacks with BIST functions
- I/O programmability for invert, amplitude, slew, pre-emphasis, and equalization
- Optional forward error correction (FEC)
- Flexible clocking options that enable Layer 1 support for Synchronous Ethernet
- · Passive copper cable support for lowest connectivity cost

Related Products

Visit <u>www.microsemi.com</u> for information about these related products:

- VSC8257 and VSC8258
- VSC8489, VSC8490, and VSC8491
- VSC8582 and VSC8584
- VSC7442, VSC7444, and VSC7448
- VSC7460, VSC7462, and VSC7468





Microsemi Corporate Headquarters One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Fax: +1 (949) 215-4996 Email: sales.support@microsemi.com www.microsemi.com Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.