ATM-10N Text Display Operator Panel



The **ATM-10N** is a super bright LCD operator interface that can store up to 128 text messages and can communicate with Aromat's FPO, FPM, and FP2. A standard overlay is included or you can customize your own.



(Standard overlay)

Key Features:

- 2 System Keys
- 4 Programmable Function Keys (Momentary, Toggle, Set, Reset)
- Scrolling and Flashing Messages
- 255 Internal Recipe Storage Variables (Built-in Recipe Storage Area)
- Bar-Graph Data Display
- 2 LED's for Alarm Annunciation
- Pass Through Communications

SOFTWARE

ATMSOFT32 is a simple programming tool that helps you build your applications quickly and easily. Whether it is a small application to monitor data or a bigger application to monitor and change data, ATMSOFT32 can do it all. This software supports

Specifications

Display High Brightness Backlit LCD

Display size 2 x 16 Characters

Character size 0.2 inches

LED 2

Function keys 6

Memory 64KB EPROM

Calendar Time Clock None

Communication port 2 Ports: DSUB-15 (PLC), DSUB-9 (PC)

Password Function Key Security

Only

Expansion slot None

Other function None

Power Supply 5VDC (From PLC Port)

Current Consumption 180mA

Ambient temperature 32 to 122 ° F(0 to 50

°C)

Ambient Humidity 90% Non Condensing

Protection (Front) IP65

Dimensions (mm) 108 (w) x 60 (h) x 44

(d)

Panel Cutout (mm) 90 (w) x 44 (h)

Communication Baud 19,200 or 9600 BPS

Rate

Ordering Information

ATM-10N ATM-10N

Programming Kit includes programming cable, software, and manual

d XKIT-ATM32-ALL

most of the FP Series PLCs.	Cable to PLC - FP0/M/2 (0.5m)	AFC15205-US
System requirements include:		
• 386 or higher	Cable to PLC - FP0/M/2 (1.5m)	AFC15215-US
Windows 3.1 or higher	Software	ATMSOFT32-CD
 Dos Version 5.0 or higher 		
 Display resolution of 640 x 480 (VGA) No EGA/CGA 	Program Cable	AFP15IBM-US