

JKL LAMP	VOLTS	AMPS	MSCP	LUMENS	AVERAGE	FILAMENT
NUMBER	RATED	±10%	±25%	±25%	LIFE HRS.	TYPE
7112	5.0	.021	.034	0.43	10,000	C-2R
7114	5.0	.060	.050	0.63	100,000	C-2R
7118	5.0	.115	.150	1.89	40,000	C-2R

NOTES:

- 1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS.
- 2. BASE MATERIAL: NYLON OR EQUIVALENT.
- 3. BASE COLOR: WHITE.
- 4. PIN MATERIAL: NICKEL WIRE, GOLD PLATED.
- 5. LAMPS TO BE 100% AGED FOR AN EQUIVALENT TO A MINIMUM OF TEN HOURS AT RATED VOLTAGES.
- 6. FINAL INSPECTION ON ALL LAMPS TO BE PER: MIL. STD. 105E TO AN AQL OF 2.5.
- 7. DIMENSIONS NOT PROVIDING TOLERANCES ARE REFERENCE DIMENSIONS ONLY.

		METRIC DIMENSIONS ARE IN MILLIMETERS											
		 (•)-[- 	TOLERANCE UNLESS OTHERWISE SPECIFIED										
	· ·			1 PL +/- 0.2		l							
			THIRD ANGLE PROJECTION	2 PL +/- 0.20		T-3/4 MICROMINIATURE BI-PIN BASED LAMPS							
				ANGLE +/- 0									
			DRAWN BY	APPV'D B	Y DATE	SIZE	FSCM NO.						
			L. WENGSTROM	BW 3/15/00		Α	55335	NO. BI-PIN T-3/4					
	7111, BB23, 7113, 7115, 7116, 7119		CADD	DAWING		SCALE		RELEAS	FD	REVISION	REV.	SHEET	
REV.			- CAD DRAWING -				DATE		DATE	NO.	ا ما		
NO.	NUMBER	DATE	MANUAL REVISIONS NOT PERMITTED			NONE		3/15/00		1	TOFT		