

# Protective covers - HC-B 24-SD-ML/FS - 1678334

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Protective cover B24, with single locking latch, protective cover material: PA, height: 21.6 mm, seal: yes, With lanyard, diameter of retaining cord eyelet: 30 mm



# **Key Commercial Data**

Packing unit	10 STK
GTIN	4 017918 151874
GTIN	4017918151874

# Technical data

#### **Dimensions**

Length	120 mm
Width	43 mm
Height	21.6 mm
Diameter of retaining cord eyelet	30 mm

### Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-20 °C 100 °C

#### General

Size	B24
Туре	For sleeve housing without single locking latch
Material	PA
Seal material	NBR
Locking latch material	High-grade steel, handle: PA-GF
Flammability rating according to UL 94	НВ
Color	gray
Seal present	yes
Connection	Plastic protective cover for short-term protection



# Protective covers - HC-B 24-SD-ML/FS - 1678334

## Technical data


## Standards and Regulations

Flammability rating according to UL 94	HB
Environmental Product Compliance	

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# **Drawings**

#### Dimensional drawing



Dimensional drawing

# Approvals

Approvals

Approvals

EAC

Ex Approvals

## Approval details

EAC RU C-DE.Al30.B.01102

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstr. 8 32825 Blomberg

Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com