

Housing - HC-ADV-B24-CHFH-1TTM25-EEE - 1408986

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

HEAVYCON ADVANCE B24 coupling housing, for M6 screw locking, salt-water-resistant aluminum, with 1 x M25 thread, straight cable outlet, without surface coating





Key commercial data

| Packing unit | 11 |
|----------------------|----------|
| Custom tariff number | 85389099 |
| Country of origin | China |

Technical data

Dimensions

| Height | 72 mm |
|--------|--------|
| Width | 45 mm |
| Length | 152 mm |

Ambient conditions

| Schutzart Gehäuse (IP) | IP65 |
|---------------------------------|---------------------|
| | IP68 (0.2 bar/24 h) |
| | IP69K |
| Ambient temperature (operation) | -40 °C 125 °C |

General

| Note | For contact inserts HC-B24, BB46, D64, DD104, M, K |
|--------------------|--|
| Design | B24 |
| Housing type | Coupling housings |
| Locking type | Screw locking |
| Fixing screws | M6 |
| No. of cable exits | 1 |
| Cable exit | Straight |



Housing - HC-ADV-B24-CHFH-1TTM25-EEE - 1408986

Technical data

General

| Screw connection | None |
|------------------------------|---|
| Type of the screw connection | 1x M25 |
| Housing material | Die-cast aluminum, salt water resistant |
| Housing surface material | Uncoated |

Classifications

eCl@ss

| eCl@ss 4.0 | 27140816 |
|------------|----------|
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27261203 |
| eCl@ss 7.0 | 27440202 |
| eCl@ss 8.0 | 27440202 |

ETIM

| ETIM 4.0 | EC000438 |
|----------|----------|
| ETIM 5.0 | EC000437 |

UNSPSC

| UNSPSC 6.01 | 31261502 |
|---------------|----------|
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Accessories

Accessories

Protective cover

Protective covers - HC-B 24-TMS-SD-IP65 - 1690804



HEAVYCON ADVANCE B24 IP65 protective cover, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm



Housing - HC-ADV-B24-CHFH-1TTM25-EEE - 1408986

Accessories

Protective covers - HC-B 24-TMS-SD-IP50 - 1690765



HEAVYCON ADVANCE IP50 protective cover B24, for panel mounting side, with clip locking, with retaining cord, diameter of retaining cord eyelet 3 mm

Drawings

Dimensioned drawing



Dimensional drawing

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com